

Preliminary results on carbon dioxide and temperature profiles from NOMAD SO

Loïc Trompet (1), Ann Carine Vandaele (1), Ian R. Thomas (1), Séverine Robert (1), Shohei Aoki (1,2,3), Justin T. Erwin (1), Arnaud Mahieux (1,2,4), Arianna Piccialli (1), Valérie Wilquet (1), Frank Daerden (1), Lori Neary (1), Sébastien Viscardy (1), Bojan Ristic (1), Bernd Funke (5), Brittany Hill (5), Miguel Ángel López-Valverde (5), Manuel López-Puertas (5), José Juan López-Moreno (5), Maya García-Comas (5), Marco Giuranna (6), Giuseppe Sindoni (6), Fabrizio Oliva (6), Giancarlo Bellucci (6), Manish R. Patel (7) and the NOMAD team
(1) Royal Belgian Institute for Space Aeronomy, Belgium, (2) Fond National de la Recherche Scientifique, Belgium, (3) Tohoku University, Japan, (4) The University of Texas at Austin, USA, (5) Instituto de Astrofísica de Andalucía, CSIC, Spain, (6) Institute for Space Astrophysics and Planetology, Italy, (7) Open University, UK. (loic.trompet@aeronomie.be)

Introduction

NOMAD (Nadir and Occultation for MARS Discovery) [1, 2] is one of the four instruments on-board the ExoMars 2016 Trace Gas Orbiter (TGO). It consists of three high-resolution spectrometers, SO, LNO and UVIS. It can operate in different geometries: solar occultation, limb and nadir. The SO channel started to make solar occultation measurements on April 21, 2018. It is performing optimally and is now regularly making solar occultation measurements of the atmosphere of Mars.

1. The NOMAD SO channel

The SO channel is dedicated to solar occultation measurements, and is a copy of the SOIR instrument [3] that operated successfully during the entire Venus Express mission. It is an infrared spectrometer working in the 2.2 to 4.3 μm spectral range (2325-4545 cm^{-1}) with a spectral resolution that varies from 0.15 to 0.2 cm^{-1} . The instrument is composed of an echelle grating in a near Littrow configuration, and an Acousto-Optical Tunable Filter (AOTF) for the diffraction order selection [4].

The orbit of TGO is circular at an altitude of 400 km. During a solar occultation, six diffraction orders are scanned every second. The spectra are recorded for each order at a one second interval and are summed in 4 bins. In this configuration, the vertical sampling of the SO channel is always smaller than 1 km.

2. Profiles retrievals

One of the radiative transfer code used to retrieve NOMAD vertical profiles is ASIMUT-ALVL [5]. This code, developed at BIRA-IASB, is based on the Optimal Estimation Method [6] and includes the

analytical calculation of the Jacobians [6]. It can be used for different geometries including solar occultations. From CO_2 vertical profiles, temperature profiles are obtained using the hydrostatic equation and the ideal gas law, similar to the work that was accomplished using the SOIR instrument spectra [7].

The preliminary results of retrieved CO_2 and temperature vertical profiles from the SO channel will be presented, discussed, and compared to results obtained by other instruments as well as models.

Acknowledgements

The NOMAD experiment is led by the Royal Belgian Institute for Space Aeronomy (BIRA-IASB), assisted by Co-PI teams from Spain (IAA-CSIC), Italy (INAF-IAPS), and the United Kingdom (Open University). This project acknowledges funding by the Belgian Science Policy Office (BELSPO), with the financial and contractual coordination by the ESA Prodex Office (PEA 4000103401, 4000121493), by MICIIN through Plan Nacional (AYA2009-08190 and AYA2012-39691), as well as by UK Space Agency through grant ST/P000886/1 and Italian Space Agency through grant 2018-2-HH.0. The research was performed as part of the “Excellence of Science” project “Evolution and Tracers of Habitability on Mars and the Earth” (FNRS 30442502). This research was supported by the FNRS CRAMIC project under grant number T.0171.16 and by the BrainBe SCOOP project.

References

- [1] Vandaele, A.C., et al.: Science objectives and performances of NOMAD, a spectrometer suite for the ExoMars TGO mission, *Planet. Space Sci.*, Vol. 119, pp 233-249, 2015.

- [2] Neefs, E., et al.: NOMAD spectrometer on the ExoMars trace gas orbiter mission: part I – design, manufacturing and testing of the infrared channels, *Appl. Opt.*, Vol. 54(28), pp 8494-8520, 2015.
- [3] Nevejans, D., et al.: Compact, high resolution space borne echelle grating spectrometer with AOTF based on order sorting for the infrared domain from 2.2 to 4.3 micrometer, *Appl. Opt.*, Vol. 45, pp 5191-5206, 2006.
- [4] Thomas, I.R., et al.: Optical and radiometric models of the NOMAD instrument part II: the infrared channels – SO and LNO, *Opt. Express*, Vol. 24(4), pp 3790-3805, 2016.
- [5] Vandaele, A.C., Kruglanski, M., De Mazière, M., Modeling and retrieval of atmospheric spectra using ASIMUT. Proceedings of the First Atmospheric Science Conference, ESRIN, Frascati, Italy, 2006.
- [6] Rodgers, C.D., Inverse method for atmospheric sounding: theory and practice. Hackensack, N.J. (Ed.), World Scientific University of Oxford, Oxford, 2000.
- [7] Mahieux, A. et al.: Densities and temperatures in the Venus mesosphere and lower thermosphere retrieved from SOIR on board Venus Express: Carbon dioxide measurements at the Venus terminator, *J. Geophys. Res.*, Vol 117, E07001, 2012.